

## Kiss



















### Kiss

# This vintage upholstery fabric is in our Natura Collection, a collection that stands for luxury and naturel fabrics.

Kiss has undergone a special production process. The linen and cotton upholstery fabric is dyed, washed and finished in a certain way that the dye stuff is 'pulled' out of the fabric to give it a nice, authentic, crafted and washed aspect.

Every meter is unique, therefor it can have variations in colour, shading and structure. While being used it enhances its character. Just like your favorite pair of jeans!

If a stain occurs, please do not rub over the fabric or the stain, because then you will rub out the dye stuff and white spots will appear (especially on dark colours). Do try to remove the stain careful with a spoon. Secondly, take a cotton kitchen towel and make it wet with lukewarm water. Wring it out and put it over the stain. Let the towel lay, so it can absorb the stain (minimum 24 or 48 hours).

Kiss is perfectly suitable for loose fitting upholstery and washable at 30 degrees (machine).

- Please note this article has a higher shrinkage than the recommended maximum 3%.
- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

**Textaafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

#### Composition

/ faceside 60%CO 40%LI / backside n/a / flatweave

#### Suitable for



Please note: colours may vary according to your screen settings.



Please note: colours may vary according to your screen settings.



winered 39

#### Kiss - Article passport

A vintage upholstery fabric of linen and cotton made with a special production process to give it a nice, authentic, crafted and washed aspect.

Available from stock in a wide range of contemporary and commercial colours.

	Product	characteristics	
-			

Productgroup	flatweave	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	60%CO 40%LI	
Composition backside	n/a	
Bonding / Coating	n/a	
Statistic code	52122310	
Dyeing method	piece dyed	
Available colours	25	
Packaging	transparent plastic	

#### **Durability specifications**

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09	
				Dry	Wet	DGM	DGM+		
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	24.000		min. 12.000	min. 16.000	В	
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4-5		min. 3-4	min. 4	А	
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5								
	light colours	CTL	grade		5	min. 4	min.5	В	
	middle colours	CTL	grade		5	min. 4	min.5	В	
	dark colours	CTL	grade	4-5		min. 4	min.5	B-C	
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	4-5	4	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A	
	middle colours	CTL	grade	4-5	3-4	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A	
	dark colours	CTL	grade	4-5	2-3	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/C	
gnitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	СТІ	СТL		ssed				

#### **Processing specifications**

Material weight in grams per linear meter  Test	± 532 Test specification	Executed by	Unit	Testresult	Norm RAL GZ 430/4:2019-01	Norm DIN EN 14
Roll length in meters	±50					
Minimum workable width in centimeters	± 138					

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	800	800	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	55,8	72,1	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	5,1	2,1	max. 5	max. 4	B/A
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		pas	sed			
	Oeko-Tex, product class II	Centexbel		certified				

#### **Cleaning specifications**

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-3,7	-2,8	n/a	n/a	B/B











- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.















creativity in fabrics

**Textaafoam b.v.**La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934 F +31(0)13 534 7586 E info@textaafoam.nl www.textaafoam.nl